




Electr. Digital External Quicktest Gauge • IP67 Electr. Digital Internal Quicktest Gauge • IP67

- with analogous and digital display
- with USB interface and with Mitutoyo interface (as accessories available)
- robust, rugged plastic housing, LCD-Display with clear digits
- housing ¹⁾ oiltight, ²⁾ water proof
- ABS and REL measuring system, red/green display for tolerance measurement
- with tungsten carbide measuring contact points, one movable contact arm
- reading in mm/inch, numeric interval switch
- incl. 1x 1.5 V Battery (type AA, art.-no.: 609282), and operation manual




D = form of measuring contact points **external**

form A carbide ball ø 1.5 mm / ø 3.0 mm	form B S / R 0,4 mm	form C disc ø 6 / 10 mm	form D disc ø 50 mm	form E carbide ball ø 1.5 mm / ø 3.0 mm



D = form of measuring contact points **inside**

form F S / R 0.4 mm	form G S / R 0.1 mm	form H carbide ball ø 0.6 mm	form K carbide ball ø 1.0 mm	form L carbide ball ø 1.0 mm



ART NO	mm	mm	form D	L mm	Hb mm	Hf mm	F min. N	F max. N	max. mm	KG	CC
external quicktest gauge											
¹⁾ 240300	0 - 10	0.005	E / ø 1.5	35	19.1	18.6	0.8	1.2	0.005	0.270	inclusive
¹⁾ 240301	0 - 10	0.005	C / ø 6.0	35	21.7	14.8	0.8	1.2	0.005	0.270	inclusive
¹⁾ 240302	0 - 20	0.01	E / ø 1.5	85	24.6	24.6	1.1	1.6	0.01	0.290	inclusive
¹⁾ 240303	0 - 20	0.01	F	85	24.6	2.5	1.1	1.6	0.01	0.290	inclusive
¹⁾ 240307	0 - 20	0.01	D	85	28.2	20.7	1.1	1.6	0.01	0.300	inclusive
²⁾ 240304	0 - 30	0.02	E / ø 3.0	115	22	22	1.0	1.5	0.02	0.380	inclusive
²⁾ 240305	0 - 30	0.02	A / ø 3.0	115	22	1	1.0	1.5	0.02	0.380	inclusive
²⁾ 240306	0 - 30	0.02	D	115	22	18	1.0	1.5	0.02	0.380	inclusive
internal quicktest gauge											
¹⁾ 240310	2.5 - 12.5	0.005	G	35	0.9	0.9	0.8	1.2	0.005	0.270	inclusive
¹⁾ 240311	5 - 15	0.005	H	35	2.5	2.5	0.8	1.2	0.005	0.290	inclusive
¹⁾ 240312	10 - 30	0.01	K	85	5.4	5.4	1.1	1.6	0.01	0.290	inclusive
¹⁾ 240313	20 - 40	0.01	K	85	7.3	7.3	1.1	1.6	0.01	0.290	inclusive
¹⁾ 240314	30 - 50	0.01	K	85	7.3	7.3	1.1	1.6	0.01	0.290	inclusive
¹⁾ 240315	40 - 60	0.01	L	85	12.2	12.2	1.1	1.6	0.01	0.290	inclusive
¹⁾ 240316	50 - 70	0.01	L	85	12.2	12.2	1.1	1.6	0.01	0.290	inclusive
¹⁾ 240317	60 - 80	0.01	L	85	12.2	12.2	1.1	1.6	0.01	0.290	inclusive
¹⁾ 240318	70 - 90	0.01	L	85	12.2	12.2	1.1	1.6	0.01	0.290	inclusive
¹⁾ 240324	80 - 100	0.01	L	85	12.2	12.2	1.1	1.6	0.01	0.330	inclusive
²⁾ 240319	13 - 43	0.02	L / ø 1.5	114	4.5	2.5	1.2	1.7	0.02	0.360	inclusive
²⁾ 240320	30 - 60	0.02	L / ø 2.0	114	8.0	4.0	1.3	1.87	0.02	0.380	inclusive
²⁾ 240321	50 - 80	0.02	L / ø 2.0	114	8.0	4.0	1.3	1.87	0.02	0.380	inclusive
²⁾ 240322	70 - 100	0.02	L / ø 2.0	114	8.0	4.0	1.3	1.87	0.02	0.380	inclusive
²⁾ 240323	90 - 120	0.02	L / ø 2.0	114	8.0	4.0	1.3	1.87	0.02	0.380	inclusive