

1
2
3e
4
5
6
7
8
9
10
11

★★★★★ DIGI PLUS-LINE® Electr. Digital 3-Point Bore Gauges • IP67

- water- and coolant proof acc. to DIN 40050 / IEC 60529
- for through holes and from up 12.5 mm for blind holes also
- Proximity-USB / RS232 output
- large LCD display with clear reading, digit height 9 mm
- bi-directional communication, ratchet stop, to ensure constant measuring force
- from up 12.5 mm with carbide measuring faces, „0“-setting at any position
- On-/Off-button, mm/inch switchable, data hold function
- 4 preset memories, simple 2-button operation
- incl. setting ring, UKAS certificates for instruments and setting rings
- incl. 1x 3 V battery (CR2032, Art.-No. 2002093), with operation manual

Options for art.-no. 230631 - 230649 + 230631-BT - 230649-BT

- with built-in Bluetooth or WiFi, see page 115
- other measuring ranges and other measuring heads available on request! extensions find on page 120

Option for art.-no. 230631 - 230649

- data transfer via WiFi, art.-no. 2023104 + 2023105, see page 304

Option for art.-no. 230631-BT - 230649-BT

- data transfer via Bluetooth, art.-no. 2023106, see page 304



ART NO with WiFi	ART NO with Bluetooth	mm / inch	mm / inch	max. mm	meas.-depth mm	ø mm	KG	CC
230631	230631-BT	6 - 8 / 0.25 - 0.3	0.001 / 0.00005	0.004	58	8.0	0.300	inclusive
230632	230632-BT	8 - 10 / 0.3 - 0.4	0.001 / 0.00005	0.004	58	8.0	0.300	inclusive
230633	230633-BT	10 - 12.5 / 0.4 - 0.5	0.001 / 0.00005	0.004	58	12.5	0.300	inclusive
230634	230634-BT	12.5 - 16 / 0.5 - 0.6	0.001 / 0.00005	0.004	62	12.5	0.300	inclusive
230635	230635-BT	16 - 20 / 0.6 - 0.8	0.001 / 0.00005	0.004	62	20.0	0.500	inclusive
230636	230636-BT	20 - 25 / 0.8 - 1	0.001 / 0.00005	0.004	66	20.0	0.500	inclusive
230637	230637-BT	25 - 35 / 1 - 1.37	0.001 / 0.00005	0.004	66	35.0	0.500	inclusive
230638	230638-BT	35 - 50 / 1.37 - 2	0.001 / 0.00005	0.004	80	35.0	1.100	inclusive
230639	230639-BT	50 - 65 / 2 - 2.55	0.001 / 0.00005	0.005	80	65.0	1.100	inclusive
230640	230640-BT	65 - 80 / 2.55 - 3.15	0.001 / 0.00005	0.005	80	65.0	1.100	inclusive
230641	230641-BT	80 - 100 / 3.15 - 4	0.001 / 0.00005	0.005	100	80.0	1.200	inclusive
230642	230642-BT	100 - 125 / 4 - 5	0.001 / 0.00005	0.006	115	125.0	2.100	inclusive
230643	230643-BT	125 - 150 / 5 - 6	0.001 / 0.00005	0.006	115	125.0	2.700	inclusive
230644	230644-BT	150 - 175 / 6 - 7	0.001 / 0.00005	0.007	115	175.0	3.500	inclusive
230645	230645-BT	175 - 200 / 7 - 8	0.001 / 0.00005	0.007	115	175.0	3.800	inclusive
230646	230646-BT	200 - 225 / 8 - 9	0.001 / 0.00005	0.008	118	225.0	3.800	inclusive
230647	230647-BT	225 - 250 / 9 - 10	0.001 / 0.00005	0.008	118	225.0	3.800	inclusive
230648	230648-BT	250 - 275 / 10 - 11	0.001 / 0.00005	0.009	118	275.0	3.800	inclusive
230649	230649-BT	275 - 300 / 11 - 12	0.001 / 0.00005	0.009	118	275.0	3.800	inclusive

★★★★★ DIGI PLUS-LINE® Electr. Digital 2-/3-Point Bore Gauge Set • IP67

- water- and coolant proof acc. to DIN 40050 / IEC 60529
- for through holes and from up 12.5 mm for blind holes also
- Proximity-USB / RS232 output
- large LCD display with clear reading, digit height 9 mm
- bi-directional communication, ratchet stop, to ensure constant measuring force
- from up 12.5 mm with carbide measuring faces, „0“-setting at any position
- On-/Off-button, mm/inch switchable, data hold function
- 4 preset memories, simple 2-button operation
- incl. setting ring, UKAS certificates for instruments and setting rings
- incl. 1x 3 V battery (CR2032, art.-no. 2002093), with operation manual

OPTIONS
see above



ART NO with WiFi	ART NO with Bluetooth	mm / inch	mm / inch	max. mm	meas.-depth mm	meas.- heads	quantity	KG	CC
2-Point Bore Gauge Set									
230611	230611-BT	2 - 6 / 0.08 - 0.25	0.001 / 0.00005	0.004	9 / 12 / 18	5	3	2.000	inclusive
3-Point Bore Gauge Sets									
230612	230612-BT	6 - 10 / 0.25 - 0.4	0.001 / 0.00005	0.004	58	2	1	2.000	inclusive
230613	230613-BT	10 - 20 / 0.4 - 0.8	0.001 / 0.00005	0.004	58 / 62	3	2	2.000	inclusive
230614	230614-BT	20 - 50 / 0.8 - 2	0.001 / 0.00005	0.004	66 / 80	3	2	3.200	inclusive
230615	230615-BT	50 - 100 / 2 - 4	0.001 / 0.00005	0.005	80 / 100	3	2	5.000	inclusive
230616	230616-BT	100 - 150 / 4 - 6	0.001 / 0.00005	0.006	115	2	1	7.000	inclusive
230617	230617-BT	150 - 200 / 6 - 8	0.001 / 0.00005	0.007	115	2	1	12.000	inclusive
230618	230618-BT	100 - 200 / 4 - 8	0.001 / 0.00005	0.006 / 0.007	115	4	2	16.000	inclusive