# Keysight Technologies U1701B Handheld Capacitance Meter

Data Sheet





The Keysight Technologies, Inc. handheld capacitance meters expand Keysight's portfolio of handheld tools into electronics assembly and passive components troubleshooting. Keysight now offers its handheld capacitance meter, the U1701B, providing extra capabilities and functionalities.

#### Features

- 11,000 counts resolution
- Dual display with backlight
- Wide range: 1000 pF to 199.99 mF
- Compare mode with 25 sets of High/Low limit settings
- Tolerance mode: 1%, 5%, 10% and 20%
- Relative mode
- Hold and Min/Max/Average recordings
- Data logging to PC with optional IR-to-USB cable

### Efficient capacitor sorting



Figure 1. Automate the recording of continuous readings when you hook the U1701B to a PC  $\,$ 

With up to 25 sets of High/Low limits that you can store and choose from in compare mode, the U1701B lets you breeze through capacitor sorting without the need to set and reset the standard reference for different capacitors-under-test.

The U1701B also comes with other handy functions, including tolerance and relative modes, Hold, Min/Max/Average recordings, and PC data logging.

### Uncompromised quality and reliability

The handheld capacitance meter comes in a robust overmold and tested to stringent industrial standards. Each capacitance meter is sealed with the assurance that you can test your components with confidence.

## Take a Closer Look



Figure 2. U1701B front view

## U1701B Electrical Specifications

Accuracy is given as  $\pm$  (% of output + counts of least significant digit) at 23 °C  $\pm$  5 °C, with relative humidity less than 80% R.H.

For example,  $1\% \pm 10 = 1\%$  of reading + 10 counts of least significant digit.

## Capacitance

Range	Resolution	Accuracy*	Measuring rate (approx.)
1000.0 pF	0.1 pF	1% + 10	5 times/s
10.000 nF	0.001 nF	1% + 5	5 times/s
100.00 nF	0.01 nF	0.5% + 3	5 times/s
1000.0 nF	0.1 nF	0.5% + 3	5 times/s
10.000 μF	0.001μF	0.5% + 3	5 times/s
100.00 μF	0.01 μF	0.5% + 3	5 times/s
1000.0 μF	0.1 μF	0.5% + 3	0.86 times/s
10.000 mF	0.001 mF	1% + 5	0.13 times/s
199.99 mF	0.01 mF	2% + 5	0.006 times/s

<sup>\*</sup> Accuracy is specified to measure film capacitor or better. Use Relative mode to zero residual.

## **General Specifications**

Parameter	U1701B		
Display	4½-digit liquid crystal display (LCD) with a maximum resolution of 11,000 counts and automatic polarity indication		
Power supply	– 9 V Alkaline battery (ANSI/NEDA 1604A or IEC 6LR61)		
	– AC power adapter and cord available as options		
Power consumption	5.6 mA (on battery operation)		
Battery life	~80 hours without backlight and based on new alkaline		
Operating temperature	Full accuracy at 0 °C to 50 °C		
Operating humidity	Up to 80% relative humidity (R.H.) for temperatures up to 31 °C, decreasing linearly to 50% R.H. at 50 °C		
Altitude	0 to 2000 m		
Storage temperature	−20 °C to 60 °C		
Storage humidity	0 to 80% R.H. non-condensing		
Temperature coefficient	0.1 x (specified accuracy)/ °C (from 0 °C to 18 °C or 28 °C to 50 °C)		
Low battery indicator	± ≡ will appear when the voltage drops below ~ 6.0 V		
Weight	320 g		
Dimensions (H x W x D)	184 mm x 87 mm x 41 mm		
Safety and EMC compliance	IEC 61010-1:2001/EN 61010-1:2001 (2nd Edition) Pollution Degree 2,		
	IEC 61326-2-1:2005/EN 61326-2-1:2006, ICES-001:2004, AS/NZS CISPR11:2004		
Calibration	One-year calibration cycle recommended		

## Ordering Information



## Standard shipped items

Standard U1701B ordering includes:


- Quick Start GuideCertificate of Calibration (CoC)Alligator clip leads9 V alkaline battery

Recommended accessories			
U1174A	Warman	Soft carrying case	
U5481A		IR-to-USB cable	
U1782A	9	SMB tweezer	
U1780A	5	Power adaptor and cord (according to country)	
U1781A	D. W.	Alligator clip leads	

## **Evolving Since 1939**

Our unique combination of hardware, software, services, and people can help you reach your next breakthrough. We are unlocking the future of technology. From Hewlett-Packard to Agilent to Keysight.







#### myKeysight

#### myKeysight

#### www.keysight.com/find/mykeysight

A personalized view into the information most relevant to you.

#### http://www.keysight.com/find/emt\_product\_registration

Register your products to get up-to-date product information and find warranty information.

**KEYSIGHT SERVICES** Accelerate Technology Adoption. Lower costs.

#### **Keysight Services**

#### www.keysight.com/find/service

Keysight Services can help from acquisition to renewal across your instrument's lifecycle. Our comprehensive service offerings—onestop calibration, repair, asset management, technology refresh, consulting, training and more—helps you improve product quality and lower costs.



### Keysight Assurance Plans

#### www.keysight.com/find/AssurancePlans

Up to ten years of protection and no budgetary surprises to ensure your instruments are operating to specification, so you can rely on accurate measurements.

#### Keysight Channel Partners

#### www.keysight.com/find/channelpartners

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

www.keysight.com/find/handheldcr

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

#### Americas

Canada (877) 894 4414 Brazil 55 11 3351 7010 Mexico 001 800 254 2440 United States (800) 829 4444

#### Asia Pacific

Australia 1 800 629 485 800 810 0189 China Hong Kong 800 938 693 India 1 800 11 2626 0120 (421) 345 Japan Korea 080 769 0800 1 800 888 848 Malaysia Singapore 1 800 375 8100 0800 047 866 Taiwan Other AP Countries (65) 6375 8100

#### Europe & Middle East

Opt. 3 (IT)

0800 0260637

For other unlisted countries: www.keysight.com/find/contactus (BP-9-7-17)



United Kingdom

www.keysight.com/go/quality Keysight Technologies, Inc. DEKRA Certified ISO 9001:2015 Quality Management System

